


- 1**
Metal canopy with related shares of distance between holes.
- 2**
Simple and practical lamp assembly: through the use of metallic ferrules, thickness 2 mm, predetermined on the glass, facilitate the installation and maintenance of the lamp without the use of tools.
- 3**
3-lines electric wire, section of cables 3x0,75 T° 180.
- 4**
Stainless steel rope crease resistant of Ø1,2 mm composed of 7x7 wires.
- 5**
Metallic lamp holders T° 300 with connection type E27.
- 6**
Diffuser in crystal glass mouth blown and handmade. Characteristic textures of glass made with technique "baloton", which consists of the insertion of air bubbles in the glass during processing, getting unique reflections on the surface of the sphere. Unleaded glass; color, when there is, is not painted but got in the mix.

SHADE FINISHING



BC

CR/TR

FRAME FINISHING



NI

ELECTRIFICATION

► E27 1x77w 220-240V 50/60Hz

ALTERNATIVES:


LED 1x10w 220-240V 50/60 Hz

ELECTRIFICATION LED

LED C 8.5W 2.700K 1x5w 220-240V 50/60Hz LED 8,5W - 12 VOLT (DRIVER INCLUDED) - 2700K - 625 LUMENS - NOT DIMMABLE

LED C 8.5W DIM 2.700K 1x5w 220-240V 50/60Hz LED 8,5W - 12 VOLT (DRIVER INCLUDED) - 2700K - 625 LUMENS - DIMMABLE

SIZE



ALTERNATIVE VERSIONS

Click on the version to go to the web version of the product
3 P, 35 D1, 35 D2, 45 D1, 45 D2, 45, GD1, GD2, G, P

MARKS:



VOLUME Mc 0,1
GROSS WEIGHT Kg 8,8
NET WEIGHT Kg 6,9



QRCODE

for download

2D drawing (DWG file)
3D design (EASM_IGES file)
Mounting instructions (PDF file)