

Perch Light Branch

UMUT YAMAC



What is more poetic and elegantly captivating than a bird perched on a branch, flirting, singing and celebrating life? We all recognize this image and steal a moment from our precious time to admire this triumph of nature and beauty.

Detailing



These sunlit birds are free to swing when softly touched. They gently glow and bring along the promise of spring.

Colours


Brass and white

Perch Light Branch / Large

Dimensions

112cm | 44.1"

41cm | 16.1"



Product

WIDTH 112cm | 44.1"

HEIGHT 53cm | 20.9"

DEPTH 41cm | 16.1"

WEIGHT NETTO 9kg | 19.84lbs

Packaging

WIDTH 34cm | 13.4"

HEIGHT 53cm | 20.9"

CUBAGE 0.21m³ | 7.32ft³

LENGTH 115cm | 45.3"

WEIGHT 9cm | 19.84lbs

Technical CE

ADDITIONAL

MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

5

SHAPE

Linear

INPUT VOLTAGE

180-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

15W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"

CANOPY

Matching steel cylinder

COLOUR TEMPERATUE

3000 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

560 lm

Technical cULus

ADDITIONAL

MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL

Energy Label B

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

5

SHAPE

Linear

INPUT VOLTAGE

90-305

FREQUENCY

50/60

MAX POWER CONSUMPTION

20W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"

CANOPY

Matching steel cylinder

COLOUR TEMPERATUE

3000 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

560 lm


Perch Light Branch / Small

Dimensions


73cm | 28.7"



24cm | 9.5"
4cm | 1.6"



36cm | 14.2"



Product

WIDTH 73cm | 28.7"

HEIGHT 53cm | 20.9"

DEPTH 36cm | 14.2"

WEIGHT NETTO 7kg | 15.43lbs

Packaging

WIDTH 36cm | 14.2"

HEIGHT 41cm | 16.1"

CUBAGE 0.14m³ | 4.85ft³

LENGTH 93cm | 36.6"

WEIGHT 7cm | 15.43lbs

Technical CE

ADDITIONAL

MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL**LIGHTSOURCE TYPE**

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

3

SHAPE

Linear

INPUT VOLTAGE

100-240

FREQUENCY

50/60

MAX POWER CONSUMPTION

15W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"

CANOPY

Matching steel cylinder

COLOUR TEMPERATUE

3000 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

336 lm

*Technical cULus***ADDITIONAL****MATERIAL**

Steel and aluminium frame with polypropylene (PP) and synthetic paper birds.

ENERGY LABEL**LIGHTSOURCE TYPE**

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

3

SHAPE

Linear

INPUT VOLTAGE

90-264

FREQUENCY

50/60

MAX POWER CONSUMPTION

20W

DIMMABLE

Yes

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"

CANOPY

Matching steel cylinder

COLOUR TEMPERATURE

3000 K

CRI

80

LIGHT DIRECTION

All directions

LIGHT OUTPUT

336 lm

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

DIMMER TYPE

1-10V

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.
