

 $\bigcirc$ 

Model: IMAGE DARK 59,6X150(A) Codes: 100293238 - P97600111 Water absorption: BIII - Revestimiento (10%<=E<=20%) Thickness: 10.5 mm





	DIMENSIONAL FEATURES UNE-EN ISO 10545-2	
Length	1500 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	10.5 MM	+/-5%*
Width	596 MM	
*ISO-13006:2018 UNE-EN 14411:2016		
	MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11	
Breaking strength	1250 N	>600N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	24.2 N/MM2	>=12N/mm2*
*ISO-13006:2018 UNE-EN 14411:2016		
	HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995	
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*
*ISO-13006:2018 UNE-EN 14411:2016		
	SCOPE OF USE	
Technical code-1	Use on walls	
	PACKING	
Boxes	2.6819 M2/BOX	
Pallets	53.6385 M2/PAL	
Units	0.894 M2/PIECE	



Do not use cleaning agents containing hydrofluoric acid. It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint. For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique. Mosaic tiles must be grouted. This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.