

Foro Ø9,5 - Opening Ø3 3/4

## Polar I



Toso, Massari & Associates, 2001

Recessed downlight available in transparent crystal or satin white suitable for installation in drywall for indoor use.





|                      |  |
|----------------------|--|
| <b>source</b>        | GU5,3 1x8W Retrofit LED 660lm (not included) A++ / B |
| <b>materials</b>     | glass, metal   |
| <b>weight-volume</b> | 0,67 kg - 0,02 m <sup>3</sup>                        |

### structure finish

-  galvanized metal
-  galvanized metal

### diffuser finish

-  satin crystal
-  transparent crystal

### code

0002852

0002849

### accessories

trasformatore elettronico 50W 12V 8000142

### notes



Transformer not included Maximum supported power: GU5,3 1xMAX 50W Halo (not included)

---





**source** GU10 1xMAX 50W Halo (not included) D  
**materials** glass, metal  
**weight-volume** 0,72 kg - 0,02 m<sup>3</sup>

**structure finish**

 galvanized metal  
 galvanized metal

**diffuser finish**

 transparent crystal  
 satin crystal

**code**  
0002850  
0002853



**notes**

---





**source** GU10 1x7W Retrofit LED MASTER 600lm (not included) A++ / A  
**materials** glass, metal  
**weight-volume** 0,72 kg - 0,02 m<sup>3</sup>

**structure finish**

 galvanized metal  
 galvanized metal

**diffuser finish**

 transparent crystal  
 satin crystal

**code**  
0002894  
0002897

**notes**

LED power max 7W with maximum length of bulb GU10=h 80.5mm

---