

THE BLISS



SPECIFICATIONS/GENERAL

| Dimensions Lx Wx H | 225 x 100 x 80 cm |
|--------------------------------|---|
| Number of Seats | 2 |
| Capacity in Liter | 450 |
| Dry Weight in kg | 150 |
| Full Weight in kg | 600 |
| Shell MaterialAristed | th® Acrylic with Vinylester and Polyester |
| Synthetic Maintenance Free Ca | binetStandard |
| Removable Side Panels | 4 |
| Cabinet Material | Synthetic |
| Durable Support System | Synthetic |
| Everlast™ Full Floor Support | MaterialPolyester |
| High Density Urethane Insulati | onStandard |

WATER SYSTEM

| Total jets | 20 | |
|---|-------------------------------|--|
| | 20 | |
| Air Injector Jets | 2 | |
| - | 2 | |
| | 50 Square Feet | |
| Side Access Skim Filter | High-Volume Side Load Skimmer | |
| Floor Drain | | |
| External Drain | I | |
| Hi Flow Suctions | 2 | |
| 5"Massage Jets, Directional, Rotational and Pulsational | | |
| 3"Directional Jets | 3 | |
| 2"Directional Jets | 14 | |
| Ozone Jets | | |

SPECIAL FEATURES

| Molded Headrest Soft Pillows with LED Light | 2 |
|--|----------|
| StarBrite Interior LED Light System | Standard |
| Cascade Creek Water Fall | Standard |
| Exterior Corner LED Lighting | 2 |
| Aromatherapy System | |
| Ozone Sanitation System | Standard |
| Synergy Water Maintenance System | Standard |
| Ultra Efficient Dual-Wrap Cabinet Insulation | Standard |
| 5/4 Ultra Efficient Walk-On Cover | Standard |
| Wifi Ready | Standard |
| • | |

PUMP INFORMATION

| Massage Pump 1:LX LP3002,2 | kW |
|------------------------------|-----|
| Filtration Pump: LX WTC50M20 | 0 W |

ELECTRICAL SYSTEM

| Voltage | 230 V |
|------------------------------|--------------|
| Amperage | |
| Full Flow Electric Heater | |
| Control System | Balboa GS100 |
| Light (18 x Multi Color LED) | |
| Electronic Topside Control | |